

# NEW: AX-E110



Excavator Mounted In-Situ  
Hydraulic Soil Mixing Attachment

For Soil Remediation or  
Stabilization Applications

Optional Wet or Dry  
Injection Systems



## BASIC SPECIFICATIONS

<b>Input Power*</b>	94 – 147 hp	70 – 110 kW
<b>Rotation Speed</b>	0 – 170 rpm	0 – 170 <sup>-1</sup>
<b>Shaft Torque (Max.)</b>	17,250 ft. lbs.	23.5 kNm
<b>Flow Requirements</b> Bi-Directional Preferred	40 – 150 gpm	150 – 565 L/min
<b>Mixing Blade Angle</b>	20° standard	(variable)
<b>Diameter with Standard Mixing Blades</b>	32"	813 mm
<b>Weight with Standard Bracket</b>	2800 lbs	1273 kg



\* Multiple Motor Power and Displacement Options to Match Carrier's Hydraulic Capacity

Specifications subject to change without prior notice



**ALPINE** SOIL MIXING SERVICES

innovative cutting solutions  
[www.alpinecutters.com](http://www.alpinecutters.com)

PO Box 681, State College, PA 16804 USA

Ph: 814.466.7134 Fax: 814.355.0046

Email: [info@alpine-aec.com](mailto:info@alpine-aec.com)